



# MB500A/C TACTICAL METAL FOREARM

MNT-HGMB500A / MNT-HGMB500C

- Fits MB 500A 12 Ga. / MB 500C 20 Ga. and Compatibles
- Made from Aircraft Aluminum and Anodized with Matte Black Finish
- Original Forearm Tolerance For Best Fit
- Combat Rated Ergonomic Features for Full Power Cocking to Carry Out Most Critical Missions
- Innovative Picatinny Rail Housing Ready for Additional Rails & Accessories

# MB500A/C TACTICAL METAL FOREARM

MNT-HGMB500A  
MNT-HGMB500C



## MB500A/C TACTICAL METAL FOREARM MNT-HGMB500A / MNT-HGMB500C

Caution: Make sure firearm is not loaded. Remove magazine and examine chamber. Use safe handling procedures at all times.



1. Set up a pleasant working environment and make the shotgun, the mount and necessary tools (a screwdriver and wrenches) available.



2. Turn the Takedown Screw counterclockwise to release its connection with the Magazine Tube.



3. Cock the gun, and pull the Barrel away from the Receiver when the Action Slide Tube Assembly is moving forward during the latter half of the cocking cycle.



7. Tighten the Action Slide Tube Nut onto the Action Slide Tube to lock the mount solidly.



8. Put the Barrel back. Tighten the Takedown Screw securely.



Action Slide Tube Nut

4. Remove the Action Slide Tube Nut by turning it counterclockwise with a screwdriver or a special tool.



5. Pull the original Forearm out from the Action Slide Tube Assembly.



6. Slide the mount onto the Action Slide Tube and make sure the rear end of the mount clamps the rear block of the Action Slide Tube Assembly.



9. (Optional) Install UTG tactical rails (MNT-P501, 502, 503, 505) on the mount for flashlight, laser or other accessory applications.